

1. 適用範圍 / SCOPE

WM55 系列小型保險絲，適用於電源模組、工業電源、通訊電源、家電、照明等。

WM55 series Miniature-Fuse, used in power module、Industrial power、communication power、appliances power、

2. lighting power.產品型號 / TYPE

例「example」：

WM55	40A	250V	
↓	↓	↓	↓
①	②	③	④

①系列號/Series Number
 ②額定電流/rated Current
 ③額定電壓/Rated Voltage
 ④安規符號/Approved Symbol


3. 額定電流和額定電壓/ RATED CURRENT AND RATED VOLTAGE

額定電流 / Rated Current: 40A~50A

額定電壓 / Rated Voltage: 250VAC / 150VDC

4. 標示 / MARKING


保險絲上需有下列標示/The fuses shall have the following marking

製造工廠的標識+系列號/ Manufacture' s Logo+ Part Number:

額定電流+額定電壓/ Rated Current (A)+ Rated Voltage(V):

順海科技
 0755-28100016



WM55
 ___A ___V AC
 ___V DC


注意 / Note:

對標示的大小和位置沒有規定 / Size and position of the markings shall not be provided.

5. 外觀及形狀 / APPEARANCES AND CONFIGURATION





5-1 外觀：不應有破碎、明顯的污斑。

Appearances: There shall not be break up and any remarkable blotch.

5-2 形狀：小型保險絲。

Configuration: Miniature-Fuse.

6. 工程圖和結構 / OUTLINE DRAWING AND STRUCTURE
6-1 工程圖 (單位: mm) / Outline Drawing and Dimensions (Unit: mm)


WM55-XXX	
WM55-XXX -P	
WM55-XXX -P-L	
WM55-XXX -P-SXL	

7. 電氣特性 / ELECTRICAL CHARACTERISTICS


Electrical Characteristics		
Rated Current	1.0In	2.5In
40A/50A	4 hour min.	120 sec max.

Specification


品名 Type	料號 Ordering P/N		額定電 壓 Rated Voltage	額定電 流 Rated Current	分斷能力 Breaking Capacity (A)		電阻 Typical Cold. Resistance (mΩ)	I ² t 值 Typical Pre- Arching I ² t (A ² Sec)
	WM55-XXX	WM55-XXX-P-YY (YY : blank / L / SXL)			AC	DC		
WM55	WM55-40	WM55-40-P-YY	250V AC 150V DC	40A	1000A	1000A	1.65	3100
	WM55-50	WM55-50-P-YY		50A	1000A	1000A	1.23	7350

冷電阻在直流<10%額定電流條件下 25℃環境溫度中測量

DC Cold Resistance are measured at <10% of rated current in ambient temperature of 25℃

I²t 值是以 10In 電流測量 Typical Pre-arching I²t are measured at 10In Current

8. 時間電流曲線 Time-Current Curve




9. 環境特性 / ENVIRONMENTAL CHARACTERISTIC

9-1 操作溫度 範圍: -40°C ~ 125°C / Operating Temperature: -40°C ~ 125°C

若 貴司操作環境溫度 超出25±5°C 範圍，在選用保險絲規格時，需考慮操作環境溫度 對保險絲的影響。
請參照：溫度-電流 曲線圖。

When choosing the fuse's specification, if the operating environmental temperature beyond the scope from 20~30°C, you should consider the environmental temperature's affection to fuses.
Please refer : Temperature-Current curve:



9-2 存儲條件 / Storage Conditions

在溫度+10°C ~ 60°C、相對濕度 ≦ 75% 的密閉條件下可存放 3 年。
Under airtight in temperature +10°C ~ 60°C, relative humidity ≦ 75% can store 3 years.

在溫度+10°C ~ 60°C、相對濕度為 95% 的非露天下最多可存放 30 天。
Without dew in temperature +10°C ~ 60°C, relative humidity be 95% maximum value for 30 days.

10. 安全認證及編號 / STANDARDS AND APPROVALS

UR	E56092 (40~50A JDYX2)
CUR	E56092 (40~50A JDYX8)

11. 安裝方式及條件 / INSTALLATION WAY AND PARAMETERS

11-1 建議如下圖安裝方式安裝，並滿足所要求的尺寸。

Propose that the following picture installation way is installed, and satisfied the required size.

11-2 建議客戶焊接參數 / Recommended Customer Soldering Parameters

波峰焊參數 / Wave Parameters:

錫爐溫度 / Solder Pot Temperature: 260±3°C

焊接時間 / Solder Dwell Time: 10s Max

手工焊參數 / Hand-Solder Parameters:

烙鐵溫度 / Solder Iron Temperature: 350±5°C


焊接時間 / Heating Time: 5 s Max

12. 包裝 / PACKING
12-1 數量 / Quantity


規格 Specs	袋 Inner polybag	小盒 Inner small box .	大盒 Inner big box	外箱 outer carton
WM55-XXX	250PCS	/	250PCS	5000 PCS
WM55-XXX-P	200PCS	/	200PCS	2000 PCS
WM55-XXX-P-L	200PCS	/	200PCS	2000 PCS
WM55-XXX-P-SXL	200PCS	/	200PCS	2000 PCS

12-2 內盒(大) / Inner big box

單位 / Unit: mm



規格 Specs	L	W	H
WM55-XXX	185±5	75±5	65±5
WM55-XXX-P	238±5	76±5	67±5
WM55-XXX-P-L	238±5	76±5	67±5
WM55-XXX-P-SXL	238±5	76±5	67±5

12-3 外箱 / Outer carton


單位 / Unit: mm

規格 Specs	L	W	H
WM55-XXX	400±5	380±5	140±5
WM55-XXX-P	410±5	250±5	160±5
WM55-XXX-P-L	410±5	250±5	160±5
WM55-XXX-P-SXL	410±5	250±5	160±5



13.其他 / OTHERS

13-1 如果在使用中有超出本規格書的要求，必須經由雙方協商確認。

In the event that an impropriety is found beyond this specification, it shall be fixed by mutual agreement between the parties.

13-2 如果本規格書有不適當的情況，必須通過雙方協商並由本公司修改。

In the event that an impropriety is found in this specification, WALTER ELECTRONIC CO., LTD. shall amend it by mutual agreement between the parties.



順海科技
0755-28100016

版次	製作	確認	審核
第四版	King	Walker	Andrew



UL iQ for Fuses



Fuses

E56092

Guide Information

SUZHOU WALTER ELECTRONIC CO LTD

NO.99 Xinli Road, Fenhu Technic Development Zone, Wujiang Jiangsu 215211 CN

WM55-XX XX represents rated current

Supplemental fuses: filled-tube

<u>Size</u> mm(in)	<u>Amps</u> (A)	<u>Volts</u> (V)	<u>Interrupting</u> <u>Rating (A)</u>
6.3 x 31.75 (0.25 x 1.25)	0.1 - 50	250Vac	1000
	0.1 - 30	660Vac	1000
	0.1 - 30	660Vdc	1000
	0.1 - 12	600Vdc	10000
	0.1 - 12	1000Vdc	10000
	0.1 - 50	150Vdc	1000
	0.1 - 12	600Vac	10000
	0.1 - 12	1000Vac	10000
	0.1 - 30	400Vac	1000
	0.1 - 30	400Vdc	1000
	0.1 - 12	300Vac	10000
	0.1 - 12	300Vdc	10000

Report Date: 2016-04-01

Last Revised: 2018-10-23

© 2021 UL LLC



顺海科技
0755-28100016



UL iQ for Fuses



Fuses

E56092

Guide Information

SUZHOU WALTER ELECTRONIC CO LTD

NO.99 Xinli Road, Fenhu Technic Development Zone, Wujiang Jiangsu 215211 CN

WM55-XXP XX represents rated current

Supplemental fuses: filled-tube

<u>Size</u> mm(in)	<u>Amps</u> (A)	<u>Volts</u> (V)	<u>Interrupting</u> <u>Rating (A)</u>
6.3 x 31.75 (0.25 x 1.25)	0.1 - 50	250Vac	1000
	0.1 - 30	660Vac	1000
	0.1 - 30	660Vdc	1000
	0.1 - 12	600Vdc	10000
	0.1 - 12	1000Vdc	10000
	0.1 - 50	150Vdc	1000
	0.1 - 12	600Vac	10000
	0.1 - 12	1000Vac	10000
	0.1 - 30	400Vac	1000
	0.1 - 30	400Vdc	1000
	0.1 - 12	300Vac	10000
	0.1 - 12	300Vdc	10000

Report Date: 2016-04-01

Last Revised: 2018-10-23

© 2019 UL LLC



顺海科技
0755-28100016